



| | | |
|----------------|--------------------------------|------------------|
| BERNATI | | |
| Scale: | Description: | Model: |
| 1:5 | Three phase asynchronous motor | BCT 280S-2 |
| | | Drawing n°: |
| | | BCT475028A205.11 |
| | | Page size: |
| | | A3 |
| | | ENG |
| | | 1/1 |

| | |
|----------------------|-------------------|
| BCT | |
| Product Code | BCT4750.28A205.11 |
| Motor Type/Frame | BCT 280S-2 |
| Mounting | IM B5 |
| Efficiency Class | IE4 |
| Output Power (kW) | 75.00 |
| Speed (rpm) | 2980 |
| Tension (V) | 230/400 |
| Frequency (Hz) | 50 |
| Current (A) | 127.20 |
| Power factor (Cos Ø) | 0.90 |
| Poles | 2 |
| Insulation Class | F |
| IP Class | IP55 |
| 50% Efficiency | 95.0 |
| 75% Efficiency | 95.8 |
| 100% Efficiency | 95.6 |
| Torque (Nm) | 240.50 |
| Tstart / Tnominal | 1.80 |
| Istart / Inominal | 8.50 |
| Tmax / Tnominal | 2.30 |
| Noise (dB) | 91 |
| PTC Thermistor | PTC 130 |
| Weight (Kg) | 625 |
| DE Bearing | 6316 C3 |
| NDE Bearing | 6316 C3 |